

PosiTest® **DFT**

Misuratore di spessore del rivestimento

Misura lo spessore del rivestimento sui metalli

modell . . .

Ferroso r

Combo r

Ideale . . .

- Powder Coaters
- Paint Applicators
- Coating Inspectors
- Painting Contractors
- Automotive Refinishers and Detailers



simply
measures

DeFelsko®
The Measure of Quality

PosiTest[®] DFT

Coating Thickness Gage

Two Models

PosiTest DFT Ferrous

- Measures non-magnetic coatings on steel

PosiTest DFT Combo

- Measures both non-magnetic coatings on steel AND non-conductive coatings on aluminum, brass, etc. Automatically recognizes the substrate and takes a measurement.

Bright, high contrast color display with large numerals for superior readability.



Actual Size

Features

- Fast, repeatable measurements — 60+ readings per minute
- Ready to measure—no adjustment required for most applications
- Zero or 1 Point Calibration Adjustment for complex applications
- Onscreen averaging for up to 99 readings
- Strong, wear-resistant, ruby-tipped probe
- V-groove in probe for positioning on cylindrical parts
- High contrast color display
- Adjustable display brightness for optimal visibility in any environment
- Auto rotating display with lock to prevent unintended rotations
- Simple, icon based menu
- Handy RESET feature when no zero reference is available
- Mils/microns switchable
- Built-in wrist strap for added convenience and safety
- Two year warranty

Measurement Range	0 – 40 mils	0 – 1000 μ m
Accuracy	$\pm(0.1 \text{ mils} + 3\%)$	$\pm(2 \mu\text{m} + 3\%)$



Auto rotating display with rotation lock

ALL GAGES COME COMPLETE

with wrist strap, precision plastic shims, hard shell storage case, 2 AAA alkaline batteries, instructions, Long Form Certificate of Calibration traceable to PTB, two year warranty.

SIZE: 108 x 43 x 20 mm (4.25" x 1.7" x 0.8")
WEIGHT: 54 g (1.9 oz.) without batteries

Conforms to ISO 2178/2360/2808, ISO 19840, ASTM B244/B499/D7091/E376, BS3900-C5, SSPC-PA2 and others

Options

Pouch with belt clip protects your PosiTest DFT while keeping it within easy reach

Coating Thickness Standards to fulfill both ISO and in-house quality control requirements

